

DIMENSIONS

(WITH TRAILER PACKAGE)

LENGTH
WIDTH
HEIGHT (max head position)
WEIGHT (with heaviest power options)

MAXIMUM CUTTING CAPACITIES¹

LOG LENGTHS
LOG DIAMETER
PRODUCTION RATES²
POWER SELECTIONS

BLADES

FEED SYSTEM
UP/DOWN
TRAILER PACKAGE
BED EXTENSIONS³
STAINLESS STEEL BED SLEEVES
LOG TURNER
TOEBOARDS
BOARD RETURN
ACCUSET® 2 SETWORKS
MANUAL WINCH
DEBARKER
LOG LOADER
BLADE LUBRICATION
WARRANTY / MONEY BACK GUARANTEE

LT10

14'4" (4.4m)
5'4¾" (1.6m)
5'10¾" (1.8m)
660 lbs (299kg)
11' (3.3m) or No Limit
24" (610mm)
up to 160 bd ft/hr (.37m³/hr)
10HP (7.5kW) Gasoline
.042" (1mm) thick x 1.25" (32mm) wide
Manual Push
Manual
N/A
Unlimited 7' sections
N/A
N/A
N/A
N/A
N/A
N/A
N/A
N/A
N/A
Water lube - manual valve
2 yr /30 Day

LT15

LT15 LT15GO LT15 WIDE

20'4" (6.2m)	22'3" (6.8m)	20'4" (6.2m)
6'3" (1.9m)	6'3" (1.9m)	6'11" (2m)
6'3" (1.9m)	9'3" (2.8m)	6'11" (2m)
1,200 lbs (544kg)	1,850 lbs (839kg)	1,520 lbs (689kg)
17'8" (5.4m) or No Limit (ALL LT15 models)		
28" (710mm)	28" (710mm)	36" (914mm)
up to 320 bd ft/hr	up to 320 bd ft/hr	up to 375 bd ft/hr
19HP (14.1kW) Gas	19HP (14.1kW) Gas	25HP (18.6kW) Gas
25HP (18.6kW) Gas	25HP (18.6kW) Gas	17HP (12.7kW) Diesel
10HP (7.5kW) Diesel	10HP (7.5kW) Diesel	
17HP (12.7kW) Diesel	17HP (12.7kW) Diesel	
10HP (7.5kW) Single or 3 phase Electric (LT15 and LT15 Wide)		
.042" (1mm) thick x 1.25" (32mm) wide (ALL LT15 models)		
Hand Crank, Power Feed (Optional) (ALL LT15 models)		
Hand Crank	Hand Crank	Hand Crank
Optional	Standard	N/A
Unlimited 6'-8" sect.	Not available	Unlimited 6'-8" sections
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	Optional	N/A
N/A	N/A	N/A
N/A	Winch	N/A
Water lube - Convenient on/off (ALL LT15 models)		
2 yr /30 Day	2 yr /30 Day	2 yr /30 Day

LT28

26'2" (8m)
6'6" (2m)
8'5" (2.6m)
2,420 lbs (1,098kg)
21' (6.4m) and up to 45' (13.7m) w/ BX
32" (810mm)
up to 350 bd ft/hr (.82m³/hr)
19HP (14.1kW) Gasoline
25HP (18.6kW) Gasoline
17HP (12.7kW) Diesel
.042" (1mm) thick x 1.25" (32mm) wide
Hand Crank, Power Feed (Optional)
Hand Crank
Standard
6', 12', 24' (Optional)
Yes
Manual (Optional)
Manual (Optional)
N/A
N/A
Optional
N/A
Winch (Optional)
Water lube - manual valve
5 yr Chassis, 2 yr /30 Day

LT35

26'2" (8m)
6'6" (2m)
8'5" (2.6m)
3,081 lbs (1,398kg)
21' (6.4m) and up to 45' (13.7m) w/ BX
32" (810mm)
up to 375 bd ft/hr (.88m³/hr)
25HP (18.6kW) Gasoline
17HP (12.7kW) Diesel
.045" (1.14mm) thick x 1.25" (32mm) wide or .042" (1mm) thick x 1.25" (32mm) wide
12V Electric-Power Feed
12V Electric
Standard
6', 12', 24' (Optional)
Yes
Manual (Optional)
Manual (Optional)
N/A
N/A
Optional
Optional
Winch (Optional), Hydraulic (Optional)
Water lube - manual valve
5 yr Chassis, 2 yr /30 Day

1 Maximum log capacity for a basic LT10 is 3,500 lbs (1,587kg), LT15 is 4,000 lbs (1,814kg), and LT28 and larger mills are 4,400 lbs. (1,996kg)

2 Published production numbers are conservative averages and will vary. Documented, higher productions have been achieved. Call for details.

3 Loading of logs heavier than 4,400 lbs. (1,996kg) [BX equipped mills] requires auxiliary log handling equipment.

* Specifications are subject to change without notice.

U.S. 800.553.0182 - Canada 877.866.0667