

DD79 DEDUSTER

"The machine has very few jams and gets the boards clean."

-Kenmar Timber
Clifton Hill, MO



The Go Fast Deduster is the solution to sawdust left on boards. Material can be fed by hand or from an inline process into the machine's hopper. An adjustable gate allows the rubber feed belt to pull the bottom board forward to the feed wheel and through the top and bottom rotating brushes.

THE DIFFERENCE: There are several features that set the Go Fast DeDuster apart from the rest, and it all starts with the brush! Our side sweeping disc brushes sweep sideways, providing cleaner boards than traditional drum brushes. They also do not require an air collection.

BOARD KNOCKER: Our famous board knocker system helps meter the boards through the machine one at a time. It breaks frozen and sticky boards apart and prevents 99% of jams!

STANDARD FEATURES

BOARD KNOCKER SYSTEM



SIDE SWEEPING DISC BRUSHES



EVERYTHING POWERED USING JUST (1) 5 HP MOTOR



FEATURES & SPECS

OPTIONS

- 5 HP Single Phase
- Line Shaft: Available Without Power Set to Run Off Line Shaft
- Infeed Rollers
- Outfeed Belt
- Sorting Table
- Stacking Rack

MACHINE SPECS

Dimensions

- Length: 79"
- Width: 34"
- Height: 58"
- Feed Belt Height: 27" - 36"
- Exit Pinch Roller Height: 34"

Capacities

- Board Width: 2" - 6 1/4"
- Board Thickness: 3/8—2.5"
- Board Length: 18" minimum

Hydraulics

- 10 Gal Reservoir Capacity
- Self Contained 5 GPM System with Variable 0-700 Feet Per Minute Feed Speed

Power

- 5 HP Electric Motor 208/230/480/3/60 TEFC
- Completely pre-wired motor starter with start/stop buttons and circuit overload protection

POPULAR OPTIONS

103 MODEL FOR LONGER MATERIAL



TAILING BELT



INFEED ROLLS



CHOPSAWS
TRIMSAWS
FIREWOOD PROCESSING
RESAWS
NOTCHERS
DEDUSTERS
MATERIAL HANDLING