

2NX DOUBLE HEAD NOTCHER



The Go Fast 2NX Double Head Notcher is a simple and heavy duty notching machine. Quickly notch boards, recycled material, entire cants, and even un-notched pallets with the cogged chain infeed system. This notcher comes standard with variable infeed speed that is adjustable from 0 - 44 FPM with the turn of a knob.

THE MOST VERSATILE NOTCHER AVAILABLE: Can't find a notcher to notch your material? Our chain fed notcher has almost unlimited length, width, and height capacity options. Not sure if the 2NX will work for you? Just give us a call!

SIMPLE MACHINE OPERATION: There is no need to worry about jams or broken sensors with the 2NX. Simply load the chain with your material, and let the cogs push it through heads.

TOOL-FREE LENGTH ADJUSTMENTS: The notching heads and fences are easily moved with the crank of handle. No tools needed!

STANDARD FEATURES

ADJUSTABLE NOTCH UP TO
3"

THE MOST VERSATILE NOTCHER
AVAILABLE-ALMOST UNLIMITED
CAPACITY OPTIONS, EVEN ENTIRE
PALLET

VARIABLE SPEED



FEATURES & SPECS

MODELS

- 48" Length Capacity Model
- 72" Length Capacity Model
- 96" Length Capacity Model
- 120" Length Capacity Model
- 144" Length Capacity Model
- 168" Length Capacity Model
- 192" Length Capacity Model

OPTIONS

Machine Options

- Automatic Inline Infeed
- Waste Conveyors
- Capacity Options
- Pallet Fixture (run assembled 2-way pallets)

System Add-On Options

- Infeed Chain/Conveyor
- Outfeed Chain/Conveyor
- Stacking Racks
- Sorting Table

MACHINE SPECS

Dimensions

- Length: Model Dimension + 24"
- Width: 73"
- Height: 56"
- Infeed Height: 40"

Power

- Cutter Head Motors: 20HP 208/230/480/3/60 TEFC
- Infeed Motor: 1-1/2 HP 208/230/480/3/60 TEFC
- VFD: For Infeed Motor Variable Speed
- Completely Pre-Wired Motor Starter with Start/ Stop Buttons and Circuit Overload Protection

Specifications

- Cutter Heads: 12" Dia x 9" Wide
- Adjustable Cutter Head Position: Adjust Length of Cut with the Turn of a Handle
- 2" Arbor and Bearings

Capacities

- Material Length: 36" to Model Dimension
- Material Width: 8" Standard
- Material Height: 2-1/2" to 4" Standard
- Infeed Speed: 0 - 44 FPM

POPULAR OPTIONS

CUSTOM CAPACITIES



WASTE CONVEYORS



POWERED SCREWS

