

Chipper - 810M

10" Capacity



Pictured is the Model 810M with a 35HP Kubota & the Standard Rain Cover



Fully Lockable Engine Vandal Cover is available as an option.

Digital Speed Sensing is available as an option.



Extra Wide 10" x 18" Infeed

Infeed Opening - 33" x 57" (1,881 sq.in.) Reduces chain sawing time!

Feed Roll Opening - 10"x18". Wide branches & Christmas trees-No Problem

Feed Roll - 21" diameter, with 1-1/4" long, replaceable blades. (600 lbs.) No slippage. Vines, prunings, palm fronds - No Problem!

Fenders - 1/4" Diamond plate with heavy duty light enclosures!

Chipper Disc - 1-1/2" x 32" diameter. Provides sufficient weight to continuously chip through large volumes of material!

Chipper Knives - Four (4) Double edged, reversible. Less down time and easily accessible!

Exhaust Chute - 360° rotation. Position chute in any direction, adjustable chip deflector, no tools necessary!

Axle - Torflex, 6,000 lb. capacity. Independent suspension for a smoother, quieter ride!

Fuel Tank - Extra large, lockable, with drain plug! Reduces frequency of refueling!

Hydraulic Tank - Extra large, lockable, with drain plug! Has fins on the outside & is painted black for dissipation of heat!

Paint - Powder coated, baked enamel. Superior weatherability and protection against discoloration!

Engine Options - Multiple choices. Select horse power, gas or diesel!



Quality of Workmanship, Innovative Design, Built to Last!

Salsco, INC.
LEADER BY DESIGN

SPECIFICATIONS AND OPTIONS - MODEL 810M, 10" X 18" CHIPPER

INFEED CHUTE:	1/4" thick steel plate sides, 57" x 33". Control bar positioned at top and side of infeed. (forward/neutral/reverse).
INFEED OPENING:	10" x 18" opening at the infeed roll.
HYDRAULIC FEED ROLL:	Large 21" diameter x 18" long, 600-lb., weighted feed roll with 14 rows of 1-1/4" long, replaceable knives, and scraper bars, powered by a hydraulic motor. Hydraulic drive to feed roll is done through #80 chain and sprockets for increased torque.
CHIPPER DISC:	1-1/2" thick x 32" diameter disc, machined and balanced, mounted on a 4-1/2" diameter steel hub with 6-exhaust blades.
CHIPPER BLADES:	Four (4) 7-1/4" x 4" x 1/2", double sided, reversible, bolted and set into 2 knife pockets.
BED KNIVES:	Two (2). 1-horizontal, 1" thick x 7" x 18" and 1-vertical, 1" thick x 8-3/8" x 9". Both knives are reversible and adjustable.
CHIPPER BEARINGS:	3" 4-bolt flange bearing. Self centering, heavy duty cast iron type.
HYDRAULIC FEED SYSTEM:	Heavy duty 1,200-lb., weighted box type feed system. Feed rate, 0-125' per minute. Hyd. hoses - 2,500-lbs., P.S.I. working, 10,000-lbs. P.S.I. burst, including hyd. pump, control valve with relief valve, hyd. motor and 15 gallon hyd. oil reservoir.
DISCHARGE:	360 Deg. swivel chute with adjustable chip deflector. No tools required for adjustment. (270-deg. stop available, if required)
FUEL TANK:	24 Gallon with lockable filler cap and shock mounted with rubber cushions on all mounting brackets.
BATTERY:	12 V automotive style, 900 cold cranks with lockable box.
AXLE:	6,000-lb. Torflex Axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other.
TIRE/WHEEL ASSEMBLIES:	Two (2) ST225/75R15, 8-ply, 28.10" dia. Max load 2,540-lbs., each. High speed, highway rib mounted on a 6-bolt white spoke wheel.
TONGUE:	3" x 4" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate with 1/4" gussets welded for extra support.
HITCH:	2-5/16" Ball, 3" Pintle, adjustable for height. Safety chains, Two (2) 3/8" links x 36" length with slip hooks.
JACK:	2,000-lb. capacity, adjustable for height with top wind swivel snap ring mount. Secures in either an up or down position.
FENDERS:	Extra heavyduty 1/4" diamond plate fenders with safety light guards.
TOOL BOX:	Lockable toolbox. 7" W x 16-3/4" L x 6" H
LIGHTS:	LED light package. License plate, stop, directional and safety. D.O.T. approved.
TRAILER:	2" x 4" rectangular tubing with support gussets and continuous welds for strength.
GUARDS/DECALS:	All Moving Parts Guarded. Full Set of Safety Decals.
PAINT:	Orange, Polyester Powder Coat Paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration. All parts painted separately.
DIMENSIONS:	4,520 LBS. 13' Long x 6' Wide x 7'7" High

OPTIONS

Hydraulic feed wheel lift	Pintle coupler, 3"	Flashing amber warning light	ENGINE OPTIONS
Speed sensing	Mud flaps	Rotation strobe light	BRIGGS & STRATTON
Live hydraulics	7-prong electric socket for tow vehicle	Swing arm mount for warning light	35HP Gas Engine Package
Spare tire mount	6-prong electric socket for tow vehicle	Cone holder on tongue	
Spare tire & rim	6-prong electric plug	Chock holders on fenders	KUBOTA
Castor wheel with 2,000-lb. Jack	12 V elec. brakes, 6,000-lb. axle with breakaway	Shut-off valve for fuel tank	35HP Diesel Engine Package
Single rear jack stand	Hyd. surge brakes, 6,000-lb. axle with actuator	Discharge swivel stop	
Ball coupler, 2-5/16"	Dual edge knives, Extra set (4 per machine)	Hydraulic pressure check Kit	VANDAL COVER FOR ENGINE
Flashing amber warning light	Tool kit to change blades	Fold down infeed tray	IS OPTIONAL

Specifications & Options Subject to Change Without Notice.

REV. 1/2013

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment:

3-1/2" - 18" Capacity, Gas, Diesel, & P.T.O., Wood/Brush Chippers
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
Shaving Mills from 14 yds. - 48 yds. Per Hour, Electric & Diesel Powered
Gas & Electric Greens Rollers - Bale Wrappers & Bale Handlers

Salsco, INC.
 LEADER BY DESIGN

105 School House Road
 Cheshire, CT 06410 U.S.A.
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com (email)