

TWC SERIES CONVEYORS



TIMBERWOLF

FIREWOOD PROCESSING EQUIPMENT



607-307-4029

www.TimberwolfEquip.com



▲ Our customers often recommend investing in a conveyor prior to upgrading their log splitters as they have an incredible ability to boost production and profit

▲ All TWC conveyors can be transported in tow and have at least 3' of vertical range

▲ All conveyors have tapered rollers for self-adjusting belt tracking

▲ Increase in your productivity for as little as \$4,500



FEATURES



Telescopic Axles

- Hydraulic lift cylinder powered by tandem center spool valve
- Provides excellent mobility and stability while in operation



Ground Skid

- Provides additional stability by anchoring to solid ground
- Lifts the roller off the ground, allowing more room for debris to fall



Modular Hopper

- Heavy-duty, bolt-on design
- Funnel-like shape makes loading logs simple
- Easily pairs with any Timberwolf log splitter



Belt

- Choose paddle belt or rough top belt, both are 20" wide
- Rubber belt fines deflector prevents debris from falling into roller
- Self-aligning tapered rollers for correct belt tracking

The TWC-16, TWC-24, and TWC-32 Conveyors are available with optional Grizzly Bars.

SPECIFICATIONS & DIMENSIONS

Base Model	TWC-12	TWC-16	TWC-24	TWC-32
Engine Power (HP)	4.9	4.9	4.9	4.9
Travel Height	5'3"	7'	8'	8'
Min Height	5'5"	7'9"	7'8"	7'5"
Max Height	8'	10'	13'2"	14'1"
Max Angle	29	29	29	29
Frame Width	1'10"	1'10"	1'10"	1'10"
Weight (lbs)	1,055	1,200	1,730	2,040

